




8" 不锈钢膜壳-普通型

8" Membrane Housing- For Commercial Water Use



参数概述/General Specifications

侧进水, 侧口数量2~8只	Side port, with qty. of 2~8 pcs
不锈钢栲贝林端部锁紧	SS victaulic coupling end closure
最大工作压力: 300PSI	Max working pressure: 300PSI
最大工作温度: 90°C	Max working temperature: 90 °C
壳体材质: 不锈钢304/316L	Housing Material: SS304/316L
端盖材质: 不锈钢304/316L	End cap material: SS 304/316L
O型圈材质: EPDM, NSF级别	O-ring material: EPDM, with NSF certificate
表面处理: 机械抛光 (240目, Ra<0.8), 喷砂	Finish: Mechanical polishing (240 mesh, Ra<0.8), Sand blast
连接形式	Connect type
--进/出水口: 栲贝林	--F/C port: Victaulic coupling
--透过水口: 内螺纹	-- Permeate port: female thread
型号: 配8040标准膜, 可装1~6支	Model: for 8040 membrane element, of 1~6 pcs



尺寸/Dimension

型号/Model	L(mm)	L1(mm)	ID(mm)	A(inch)	B(inch)
JD-8040-1	1286	1060	Φ203	1.5~3"	1" T
JD-8040-2	2302	2076	Φ203	1.5~3"	1" T
JD-8040-3	3318	3096	Φ203	1.5~3"	1" T
JD-8040-4	4334	4108	Φ203	1.5~3"	1" T
JD-8040-5	5350	5124	Φ203	1.5~3"	1" T
JD-8040-6	6366	6140	Φ203	1.5~3"	1" T